

ARCHITECTURAL SPECIFICATIONS PANASONIC ADVANCED VENTILATION SERIES



SUPER LOW PROFILE CEILING/WALL MOUNTED VENTILATING FANS

FV-05VS1 WhisperValue

Ventilating fan and light shall be of the ceiling or wall mount, ENERGY STAR rated type, with no less than 50 CFM and no more than 0.8 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge. Fan power consumption shall be no greater than 15.8 watts and ENERGY STAR rated with efficiency rating of no less than 3.2 CFM/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 3". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Fan shall be California Title-24 compliant.

FV-08VS1 WhisperValue

Ventilating fan and light shall be of the ceiling or wall mount, ENERGY STAR rated type, with no less than 80 CFM and no more than 1.4 sones as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge. Fan power consumption shall be no greater than 23.6 watts and ENERGY STAR rated with efficiency rating of no less than 3.4 CFM/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 3". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Fan shall be California Title-24 compliant.